


Double-Ended Shear Beam

FEATURES

- Capacities 1k–75k lbs
- Double-ended center-load shear beam design
- Rationalized outputs
- Free of horizontal movement
- Insensitive to side load
- Electroless nickel-plated alloy tool steel
- **Optional**
 - Hermetically sealed version available
 - Stainless steel version available
 - FM approval available
 - EDOC option available; product appearance will differ from the photograph due to coating



APPLICATIONS

- Silo/hopper/tank weighing

The double-ended mounting provides good restraint to possible movement of the tanks and, in many cases, eliminates the need for check rods.


DESCRIPTION

The Model DSR is constructed of alloy tool steel and is potted to IP67 providing excellent protection against moisture and humidity.

The shear beam design gives excellent performance for high capacity loading.

The output is rationalized to facilitate multiple-cell application.

OUTLINE DIMENSIONS



Wiring

+ Excitation	Red
– Excitation	Black
+ Signal	Green
– Signal	White

CAPACITY		L	L ₁	L ₂	W	H	H ₁	D	D ₁	R
1k / 1.5k / 2k / 2.5k / 3k / 5k lbs	mm	190.5	158.8	35.4	31.7	31.7	-	31.7	12.7	5.0
	(inch)	7.50	6.25	1.39	1.25	1.25	-	1.25	0.50	0.20
10k / 15k / 20k / 25k lbs	mm	222.3	190.5	50.0	36.6	49.3	-	50.8	20.6	5.0
	(inch)	8.75	7.50	1.97	1.44	1.94	-	2.00	0.81	0.20
50k / 75k lbs	mm	342.9	292.1	82.6	62.0	74.7	4.6	76.2	33.3	5.0
	(inch)	13.50	11.50	3.25	2.44	2.94	0.18	3.00	1.31	0.20

Above dimensions apply to non-EDOC-coated load cells.

Double-Ended Shear Beam

SPECIFICATIONS		
PARAMETER	VALUE	UNIT
NTEP/OIML accuracy class	Non-Approved	
$Y = E_{\max}/V_{\min}$	5000	Maximum available
Standard capacities (E_{\max})	1k, 1.5k, 2k, 3k, 5k, 10k, 15k, 20k, 25k, 50k, 75k	lbs
Rated output – R.O.	3.0	mV/V
Rated output tolerance	0.25	±% of rated output
Zero balance	1	±% of rated output
Non-linearity	0.030 (SS: 0.07%)	±% of rated output
Hysteresis	0.030 (SS: 0.07%)	±% of rated output
Non-repeatability	0.02	±% of rated output
Creep error (20 minutes)	0.030	±% of rated output
Zero return (20 minutes)	0.030	±% of rated output
Temperature effect on min. dead load output	0.0026	±% of rated output/°C
Temperature effect on sensitivity	0.0015	±% of applied load/°C
Compensated temperature range	-10 to +40	°C
Operating temperature range	-20 to +60	°C
Safe overload	150	% of R.C.
Ultimate overload	300	% of R.C.
Excitation, recommended	10	VDC or VAC RMS
Excitation, maximum	15	VDC or VAC RMS
Input impedance	770±10	Ω
Output impedance	700±5	Ω
Insulation resistance	>5000	MΩ
Construction	Nicke-plated alloy steel	
Environmental protection	IP67	

All specifications subject to change without notice.

FM Approval

Intrinsically Safe: Class I, II, III; Div. 1 Groups A-G

Non-Incendive: Class I; Div. 2 Groups A-D



Disclaimer

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Vishay Precision Group, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "VPG"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

The product specifications do not expand or otherwise modify VPG's terms and conditions of purchase, including but not limited to, the warranty expressed therein.

VPG makes no warranty, representation or guarantee other than as set forth in the terms and conditions of purchase. **To the maximum extent permitted by applicable law, VPG disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.**

Information provided in datasheets and/or specifications may vary from actual results in different applications and performance may vary over time. Statements regarding the suitability of products for certain types of applications are based on VPG's knowledge of typical requirements that are often placed on VPG products. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. You should ensure you have the current version of the relevant information by contacting VPG prior to performing installation or use of the product, such as on our website at vpgsensors.com.

No license, express, implied, or otherwise, to any intellectual property rights is granted by this document, or by any conduct of VPG.

The products shown herein are not designed for use in life-saving or life-sustaining applications unless otherwise expressly indicated. Customers using or selling VPG products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify VPG for any damages arising or resulting from such use or sale. Please contact authorized VPG personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

Copyright Vishay Precision Group, Inc., 2014. All rights reserved.